# **MSDS** Document

# **Product BOSS® 333 Triple Expanding Sealant**

# 1. Chemical Product and Company Identification

Trade Name of this Product BOSS® 333 Triple Expanding Sealant

**Synonyms:** 01551BR10, 02455BR10

## MSDS ID BOSS333

ManufacturerPhone NumberAccumetric, LLC(270) 769-3385350 Ring RoadEmergency Phone

Elizabethtown, KY 42701 CHEMTREC (800) 424-9300 **Revision Date** 1/22/2007

# 2. Composition and Information on Ingredients

Ingredient Polymeric diphenylmethane diisocyanate	<b>CAS Number</b> 9016-87-9	<b>Weight %</b> > 25 %	ACGIH TLV 0.005 ppm	<b>PEL</b> 0.02 mg/m	STEL
Isobutane	75-28-5	1% - 5%			
Propane	74-98-6	1% - 5%	1000 ppm	1000 ppm PEL	
Dimethyl ether	115-10-6	1% - 15%		400 ppm	

### 3. Hazard Identification

#### Overview

Extremely flammable.

Harmful by inhalation.

Irritating to eyes, respiratory systems and skin.

May cause sensitization by inhalation and skin contact.

### **Acute Effects/Symptoms of Overexposure**

**EYE CONTACT** 

Irritation of the eye tissue, lacrimation.

### **INHALATION**

Dry/sore throat, coughing, irritation of respiratory tract, irritation of the nasal mucous membranes, runny nose.

Following symptoms may appear later: Inflammation of the respiratory tract, risk of lung

Page 2 7 Print Rev. Date 02/27/2007 MSDS ID BOSS333 BOSS® 333 Triple Expanding Sealant

edema, respiratory difficulties.

#### SKIN CONTACT

Tingling/irritation of skin.

### **Chronic Effects/Symptoms of Overexposure**

May cause sensitization by skin contact. May cause sensitization by inhalation. Contains substance with uncertain carcinogenic properties (polymethylenepolyphenylisocyanate).

The following may also occur with continuous exposure/contact:

Body temperature rise, tremor, feeling of weakness, headache, skin rash/inflammation, may stain the skin, dry skin, risk of pneumonia.

### 4. First Aid Information

### **Eye Contact**

Immediately flush eyes with large amounts of water for at least 15 minutes. Get immediate medical attention.

### Ingestion

DO NOT induce vomiting. DO NOT attempt to give anything by mouth to an unconscious person. If individual is conscious, give water to dilute stomach contents. Get prompt medical attention.

#### Inhalation

Remove to fresh air. If breathing is difficult, give oxygen. If breathing has stopped, give artificial respiration. Get medical attention.

### **Skin Contact**

Rinse immediately with plenty of water. If irritation persists, seek medical attention.

# 5. Fire Fighting Measures

Flash Point < 32°F

### **Extinguishing Media**

Carbon dioxide, BC powder, Polyvalent foam, Quantities of water

# **Unsuitable Extinguishing Media**

None known

### **Special Exposure Hazards**

On burning product releases toxic and corrosive gases/vapors: hydrogen chloride, carbon monoxide and carbon dioxide. Gas/vapor spreads at floor level, creating an ignition hazard. Gas/vapor flammable with air within explosion limits. Aerosol may explode when expose to flame or heat.

#### **Special Fire Fighting Procedures**

Dilute toxic gases with water spray. Take account of toxic fire fighting water. Do not move the load if expose to heat.

Page 3 7 Print Rev. Date 02/27/2007 MSDS ID BOSS333 BOSS® 333 Triple Expanding Sealant

### 6. Accidental Release Measures

### Steps to be taken in case of spill or release

Observe all personal protection equipment recommendations. Allow product to solidify and remove it by mechanical means. Remove uncured foam with acetone. Use appropriate containment to avoid environmental contamination.

Local, state and federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which federal, state and local laws and regulations are applicable.

# 7. Handling and Storage

#### Handling

Observe very strict hygiene. Avoid contact with skin and eyes. In case of insufficient ventilation, keep naked flames/sparks away. Remove contaminated clothing immediately. Clean contaminated clothing before re-use.

### **Storage**

Keep out of direct sunlight. Keep away from heat sources, ignition sources, acids and bases.

Storage temperature: < 122F (50C)

# 8. Exposure Controls and Personal Protection

### **Component Exposure Limits**

Polymethylenepolyphenylisocyanate (9016-87-9)

TLV-TWA: --TLV-STEL: --TLV-Ceiling: --

Dimethyl ether (115-10-6)

TLV-TWA: --TLV-STEL: --TLV-Ceiling: --

Propane (74-98-6) TLV-TWA: 2,500 ppm

TLV-STEL: --TLV-Ceiling: --

Isobutane (75-28-5)

TLV-TWA: --TLV-STEL: --TLV-Ceiling: --

# **Occupational Exposure Controls**

Use only in well ventilated areas.

Page 4 7 Print Rev. Date 02/27/2007 MSDS ID BOSS333 BOSS® 333 Triple Expanding Sealant

### **Eye Protection**

Use proper protection - safety glasses as a minimum.

#### **Skin Protection**

Chemically resistant gloves and suitable protective clothing.

### **Respiartory Protection**

In case of insufficient ventilation, use respiratory protection with filter Type A.

# 9. Physical and Chemical Properties

Physical State Aerosol
Specific Gravity 0.996
Density Ibs/Gal. 8.3120226
Color/Appearance Cream/tan
Boiling/Cond. Point Not Applicable
Melting/Freezing Point Solubility Insoluble

#### Note

The above information is not intended for use in preparing product specifications. Contact Accumetric LLC before writing specifications.

# 10. Stability and Reactivity

#### **Materials to Avoid**

Keep away from heat sources, ignition sources, acids, and bases.

### **Conditions to Avoid - Reactivity**

Unstable on exposure to heat.

### **Hazardous Decomposition Products**

On burning: release of toxic and corrosive gases/vapors: hydrogen chloride, carbon monoxide and carbon dioxide.

On heating: release of toxic /combustible gases/vapors (hydrogen cyanide).

May polmerize on exposure to temperature rise.

May polymerize with a lot of compounds, ex; (Strong) bases and amines.

Reacts violently with (some) acids/bases.

# 11. Toxicological Information

### **Acute Toxicity**

Polymethylenepolyphenylisocyanate (9016-87-9)

LD50 oral rat: > 10,000 mg/kg LD50 dermal rabbit: > 5,000 mg/kg

Page 5 7 Print Rev. Date 02/27/2007 MSDS ID BOSS333 BOSS® 333 Triple Expanding Sealant

LC50 inhalation rat: Not determined

Propane (74-98-6)

LD50 oral rat: Not determined LD50 dermal rabbit: Not determined LC50 inhalation rat: 513 mg/l/4 h LC50 inhalation rat: 280,000 ppm/4 h

Isobutane (75-28-5)

LD50 oral rat: Not determined LD50 dermal rabbit: Not determined LC50 inhalation rat: 658 mg/l/4 h

### **Chronic Toxicity**

Polymethylenepolyphenylisocyanate (9016-87-9)

Carcinogenicity (MAK): Category 3B Mutagenicity (MAK): Not Listed Teratogenicity (MAK): Group -

IARC Classification: 3

Dimethyl Ether (115-10-6)

Carcinogenicity (MAK): Not Listed Mutagenicity (MAK): Not Listed Teratogenicity (MAK): Group D IARC Classification: Not Listed

# 12. Ecological Information

### **Ecotoxicity**

No data available

# Mobility

Insoluble in water

### **Persistence and Degradability**

Biodegradation: Not determined Water: No data available Soil: Not determined

#### **Bioaccumulative Potential**

Not established

#### **Other Adverse Effects**

Effect on Ozone Layer: Not danagerous for the ozone layer (1999/45/EC)

Greenhouse Effect: No data available

Effect on Waste Water Purification: No data available

# 13. Disposal Considerations

### **Waste Disposal Method**

We make no guarantee or warranty of any kind that the use or disposal of this product

Page 6 7 Print Rev. Date 02/27/2007 MSDS ID BOSS333 BOSS® 333 Triple Expanding Sealant

complies with all local, state, or federal laws. It is also the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable statutes.

This product is not known to be regulated under RCRA regulations, but contains SARA regulated substances. Disposal of unused portions of this product and process waste containing this product should be done only after a careful evaluation and in compliance with all federal, local and state laws.

# 14. Transportation Information

## **DOT Road Shipment Information**

Hazard Class: 2.1

Identification Number: UN1950

Packing Group: -

Proper Shipping Name: AEROSOLS, flammable, n.o.s.

Label: 2.1

# Air Shipment (IATA)

ICAO/IATA Class: 2.1 UN/ID Number: 1950

Label: 2.1

Packaging Group: -

Proper Shipping Name: AEROSOLS, flammable, n.o.s.

### Ocean Shipment (IMDG)

Hazard Class: 2.1 UN Number: 1950

Label: 2.1
Packing Group: EMS Number: 2-13
Marine Pollutant: No

# 15. Regulatory Information

The contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

#### **TSCA Status**

All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

# SARA Title III Section 302 Extremely Hazardous Substances

None

### SARA Title III Section 304 CERCLA Hazardous Substances

None

### **SARA Title III Section 313 Toxic Chemicals**

Polymeric diphenylmethane diisocyanate (9016-87-9)

Page 7 7 Print Rev. Date 02/27/2007 MSDS ID BOSS333 BOSS® 333 Triple Expanding Sealant

# 16. Other Information

# **Disclaimer**

The data contained herein is based upon information that Accumetric LLC believes to be reliable. Users of this product have the responsibility to determine that suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements to suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.