



LAWSON Products

SECTION 1. IDENTIFICATION

Product name : FLEXSEAL RTV CLEAR

Product code : 91784

Manufacturer or supplier's details

Company name of supplier : Lawson Products

Address : 8770 West Bryn Mawr Ave., Suite 900
Chicago, IL 60631

Telephone : 773-304-5050

Emergency telephone : 888-426-4851

Recommended use of the chemical and restrictions on use

Recommended use : Adhesive, binding agents

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Not a hazardous substance or mixture.

GHS Label element

Not a hazardous substance or mixture.

Precautionary Statements : **Prevention:**
P271 Use only outdoors or in a well-ventilated area.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Silicone elastomer

Hazardous ingredients

| Chemical Name | CAS-No. | Concentration (%) |
|--|------------|-------------------|
| Silicon dioxide | 7631-86-9 | >= 5 - < 10 |
| Distillates (petroleum), hydrotreated middle | 64742-46-7 | >= 5 - < 10 |

SECTION 4. FIRST AID MEASURES

If inhaled : If inhaled, remove to fresh air.

| | |
|---|---|
| | Get medical attention if symptoms occur. |
| In case of skin contact | : Wash with water and soap as a precaution. Get medical attention if symptoms occur. |
| In case of eye contact | : Flush eyes with water as a precaution. Get medical attention if irritation develops and persists. |
| If swallowed | : If swallowed, DO NOT induce vomiting. Get medical attention if symptoms occur. Rinse mouth thoroughly with water. |
| Most important symptoms and effects, both acute and delayed | : None known. |
| Protection of first-aiders | : No special precautions are necessary for first aid responders. |
| Notes to physician | : Treat symptomatically and supportively. |

SECTION 5. FIRE-FIGHTING MEASURES

| | |
|--|---|
| Suitable extinguishing media | : Water spray Alcohol-resistant foam Dry chemical Carbon dioxide (CO ₂) |
| Unsuitable extinguishing media | : None known. |
| Specific hazards during fire fighting | : Exposure to combustion products may be a hazard to health. |
| Hazardous combustion products | : Carbon oxides Silicon oxides Formaldehyde |
| Specific extinguishing methods | : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so. Evacuate area. |
| Special protective equipment for fire-fighters | : Wear self-contained breathing apparatus for firefighting if necessary. Use personal protective equipment. |

SECTION 6. ACCIDENTAL RELEASE MEASURES

| | |
|-------------------------------|--|
| Personal precautions, protec- | : Follow safe handling advice and personal protective equip- |
|-------------------------------|--|

| | | |
|---|---|---|
| tive equipment and emergency procedures | : | ment recommendations. |
| Environmental precautions | : | Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained. |
| Methods and materials for containment and cleaning up | : | Soak up with inert absorbent material. For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements. |

SECTION 7. HANDLING AND STORAGE

| | | |
|-----------------------------|---|--|
| Technical measures | : | See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section. |
| Local/Total ventilation | : | Use only with adequate ventilation. |
| Advice on safe handling | : | Handle in accordance with good industrial hygiene and safety practice. Take care to prevent spills, waste and minimize release to the environment. |
| Conditions for safe storage | : | Keep in properly labeled containers. Store in accordance with the particular national regulations. |
| Materials to avoid | : | Do not store with the following product types: Strong oxidizing agents |

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

| In gr ed i e n t | C A S- N | Va lu e | C on tro l | Ba sis |
|------------------------------------|---------------------|-------------------|-----------------------|------------------|
| Sil ic on di | 76 31 - 86 | T W A (D | 20 Mi lli on | O S H A |

SAFETY DATA SHEET

| | | | | |
|---|------------|------------|---|-----------|
| | | TWA (Dust) | 80 mg/m ³ / %SiO ₂ (Silica) | OSHA Z-3 |
| | | TWA | 6 mg/m ³ (Silica) | NIOSH REL |
| Distillates (petroleum), hydrotreated middle | 64742-46-7 | TWA (Mist) | 5 mg/m ³ | OSHA Z-1 |
| | | TWA (Mist) | 5 mg/m ³ | OSHA P0 |
| | | TWA (Mist) | 5 mg/m ³ | NIOSH REL |
| | | ST (Mist) | 10 mg/m ³ | NIOSH REL |

Engineering measures : Processing may form hazardous compounds (see section 10).
Ensure adequate ventilation, especially in confined areas.
Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection

Remarks : Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
Safety glasses

Skin and body protection : Skin should be washed after contact.

Hygiene measures : Ensure that eye flushing systems and safety showers are located close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.
These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : paste

Color : colorless

| | |
|---|--|
| Odor | : Acetic acid |
| Odor Threshold | : No data available |
| pH | : Not applicable |
| Melting point/freezing point | : No data available |
| Initial boiling point and boiling range | : Not applicable |
| Flash point | : > 100 °C Method: closed cup |
| Evaporation rate | : Not applicable |
| Flammability (solid, gas) | : Not classified as a flammability hazard |
| Upper explosion limit | : No data available |
| Lower explosion limit | : No data available |
| Vapor pressure | : Not applicable |
| Relative vapor density | : No data available |
| Relative density | : 1.007 |
| Solubility(ies) | |
| Water solubility | : No data available |
| Partition coefficient: n-octanol/water | : No data available |
| Autoignition temperature | : No data available |
| Decomposition temperature | : No data available |
| Viscosity | |
| Viscosity, dynamic | : Not applicable |
| Explosive properties | : Not explosive |
| Oxidizing properties | : The substance or mixture is not classified as oxidizing. |
| Molecular weight | : No data available |

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

| | |
|------------------------------------|--|
| Chemical stability | : Stable under normal conditions. |
| Possibility of hazardous reactions | : Use at elevated temperatures may form highly hazardous compounds. Can react with strong oxidizing agents. Acetic acid is formed upon contact with water or humid air. When heated to temperatures above 150 °C (300 °F) in the presence of air, trace quantities of formaldehyde may be released. Adequate ventilation is required. See OSHA formaldehyde standard, 29 CFR 1910.1048 Hazardous decomposition products will be formed at elevated temperatures. |
| Conditions to avoid | : None known. |
| Incompatible materials | : Oxidizing agents |
| Hazardous decomposition products | |
| Thermal decomposition | : Formaldehyde |

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute inhalation toxicity : Acute toxicity estimate: > 10 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Calculation method

Ingredients:**Silicon dioxide:**

Acute oral toxicity : LD50 (Rat): > 3,300 mg/kg
Assessment: The substance or mixture has no acute oral toxicity
Remarks: Information taken from reference works and the literature.

Acute inhalation toxicity : LC50 (Rat): > 2.08 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: Information taken from reference works and the

literature.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: Information taken from reference works and the literature.

Distillates (petroleum), hydrotreated middle:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 1.78 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Ingredients:

Silicon dioxide:

Result: No skin irritation

Remarks: Information taken from reference works and the literature.

Serious eye damage/eye irritation

Not classified based on available information.

Ingredients:

Silicon dioxide:

Result: No eye irritation

Remarks: Information taken from reference works and the literature.

Respiratory or skin sensitization

Skin sensitization: Not classified based on available information.

Respiratory sensitization: Not classified based on available information.

Ingredients:

Silicon dioxide:

Assessment: Does not cause skin sensitization.

Test Type: Skin: test type not specified

Species: Guinea pig

Remarks: No known sensitising effect.

Information taken from reference works and the literature.

Germ cell mutagenicity

Not classified based on available information.

Ingredients:

Silicon dioxide:

Genotoxicity in vitro : Result: negative

Remarks: Information taken from reference works and the literature.

Genotoxicity in vivo : Application Route: Ingestion
Result: negative
Remarks: Information taken from reference works and the literature.

Germ cell mutagenicity - Assessment : Animal testing did not show any mutagenic effects.

Carcinogenicity

Not classified based on available information.

IARC

No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Ingredients:

Distillates (petroleum), hydrotreated middle:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Resource Conservation and Recovery Act (RCRA) : This product has been evaluated for RCRA characteristics and does not meet the criteria of hazardous waste if discarded in its purchased form.

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION**International Regulation****UNRTDG**

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation**49 CFR**

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION**EPCRA - Emergency Planning and Community Right-to-Know****CERCLA Reportable Quantity**

| Ingredients | CAS-No. | Component RQ (lbs) | Calculated product RQ (lbs) |
|------------------|----------|--------------------|-----------------------------|
| Acetic acid | 64-19-7 | 5000 | * |
| Acetic anhydride | 108-24-7 | 5000 | * |

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : No SARA Hazards

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations

Pennsylvania Right To Know

| | | |
|--|------------|-----------|
| Dimethyl siloxane, hydroxy-terminated | 70131-67-8 | 70 - 90 % |
| Silicon dioxide | 7631-86-9 | 5 - 10 % |
| Distillates (petroleum), hydrotreated middle | 64742-46-7 | 5 - 10 % |
| Acetic acid | 64-19-7 | 0 - 0.1 % |
| Acetic anhydride | 108-24-7 | 0 - 0.1 % |

New Jersey Right To Know

| | | |
|--|------------|-----------|
| Dimethyl siloxane, hydroxy-terminated | 70131-67-8 | 70 - 90 % |
| Silicon dioxide | 7631-86-9 | 5 - 10 % |
| Distillates (petroleum), hydrotreated middle | 64742-46-7 | 5 - 10 % |

California Prop 65 : This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

The ingredients of this product are reported in the following inventories:

REACH : All ingredients (pre-)registered or exempt.

TSCA : All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

AICS : All ingredients listed or exempt.

IECSC : All ingredients listed or exempt.

PICCS : All ingredients listed or exempt.


Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), NECSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

NFPA:



HMIS III:

| | |
|---|---|
| H | 1 |
| F | 1 |
| P | 0 |
| H | |

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

Full text of other abbreviations

| | |
|--|---|
| NIOSH REL | : USA. NIOSH Recommended Exposure Limits |
| OSHA P0 | : USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 |
| OSHA Z-1 | : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants |
| OSHA Z-3 | : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts |
| NIOSH REL / TWA | : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek |
| NIOSH REL / ST | : STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday |
| OSHA P0 / TWA | : 8-hour time weighted average |
| OSHA Z-1 / TWA | : 8-hour time weighted average |
| OSHA Z-3 / TWA | : 8-hour time weighted average |
| Sources of key data used to compile the Material Safety Data Sheet | : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, http://echa.europa.eu/ |
| Revision Date | : 02/11/2015 |

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations

in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8